

**TOWN OF ROCKLAND SPECIFICATIONS
FOR DRIVEWAYS AND RIGHTS OF WAY
ADJOINING TOWN HIGHWAYS**

1.

All driveway culvert pipe(s) with necessary collars must be furnished by applicant. Pipe must be new or in a condition acceptable to the Highway Superintendent. The size of the pipe is to be determined by the Highway Superintendent. The length of the pipe installation shall be 28 feet minimum, not exceeding 40 feet maximum. If conditions warrant a deviation from above specifications, approval must be obtained from the Highway Superintendent.

2.

DRIVEWAY: Grades shall be constricted to slope downward from the traveled portion of highway to the ditch line. The slope shall be a minimum of one half inch per foot.

3.

Driveways must have suitable drainage ditches and are to be crowned no less than one-quarter inch per foot.

4.

Drainage of highway ditches shall not be impeded. Driveway pipes must be installed to conform to the existing grade of ditch or drainage line.

5.

PIPES: Depth or installation when crossing the road shall not be less than four and one half feet.

6.

Water lines shall be contained within a sleeve so that future replacements can be made without disturbing the Highway.

7.

All work performed within Town right of way shall be inspected by the Highway Superintendent or his agent.

8.

Any material removed during excavation must be removed and replaced with Crusher Run or Item #4. All Bituminous covering must be replaced within 48 hours of Highway opening.

9.

The applicant shall be responsible for Traffic Control. Damages resulting in bodily injury including death and/or property damage due to activities of applicant or his agents, shall be the responsibility of the applicant, who agrees.

10.

The Highway Superintendent, upon failure of the applicant or landowner to comply with any of the conditions contained herein, shall remove any pipes, hydrants, culverts, driveways and other miscellaneous structures within bounds of Town Highway at owner expense.

11.

Sight distances shall be no less than 250 feet unless otherwise approved by the Highway Superintendent.